



SETO LED SNAKE SERIES

Minimizes the cost of temporary pathway lighting



The **SETO LED SNAKE** series minimises the effort for temporary construction route lighting. Long corridors or staircases and lift shafts can be illuminated with the **LED rope lights** within a very short time.

For this purpose, the flexible and highly robust LED rope light is simply rolled out and attached to the ceiling of a corridor with clips or reversible adhesive tape, or suspended in the stairwell. Depending on the size of the area to be illuminated, several ropes can also be combined so that the required illumination is always achieved (total length not more than 50 metres, not more than 600 watts power consumption per connection cable).

Thanks to the high power of 12 watts per metre, distributed over 180 LEDs per metre, the LED rope lights of the **SETO LED SNAKE** series achieve a previously unattained luminous intensity. This is also homogeneously distributed in the area to be illuminated thanks to the slight diffusion of the rope material.

PRODUCT FEATURES

- Extremely bright
- Highly robust and flexible
- Various mounting accessories available

OPTIONAL ACCESSORIES

- Connection cable 1.5 m + connector
- Clips (screwable)
- T-connector
- End cap
- Hose connector
- SETO LED SNAKE connection cable standard
- T-Connector (round)

- Item no. 1428003020
- Item no. 1428003021
- Item no. 1428003022
- Item no. 1428003023
- Item no. 1428003024
- Item no. 1428003028
- Item no. 1428003031

TECHNICAL DATA

Electrical data	SETO LED SNAKE 5/60	SETO LED SNAKE 10/120	SETO LED SNAKE 25/300	SETO LED SNAKE 50/600
Input voltage	230 V			
Power consumption	60 W	120 W	300 W	600 W
Lighting data				
Luminant	High-power LED 180 pcs. per metre			
Light colour	5.000 K			
General data				
IP Class	Converter IP54 / Rope IP67			
Protection class	II			
Connection	Without plug	Schuko, IP44		
Length	5 m	10 m	25 m	50 m
Item no.	1428003012	1428003013	1428003001	1428003002